







Features & Parameters

- O Built in 3.7V 900mAh Li-ion batteries
- O High efficiency DC 9V DC2DC Boost convertor
- O RED LED Lo battery indication
- O Yellow LED Charge indication
- O Green LED 9V Output indication
- O USB charge cable and standard DC 5V charge voltage
- O Short circuit protection

- Output Voltage: 8.55 to 9.45V
- O Max Continuous Output Current: 260mA
- O Batteries capacity: 3.7V 900mAh
- O Charging Current: 370mA
- \bigcirc Charging Voltage: DC 5V
- O Charging Time: 2.5 to 3Hours
- O Discharging time: 6H @ 50mA

Notes:

- 1, Before first use, please charge 2 to 3 hours.
- 2, When short circuit occurs, it may cause no output, at this time, please recharge the box, then it will restore the output.
- 3, Charging voltage is USB 5V 370mA, do not use other voltage to charge the box.

Contact us

INHAOS Headquarter: :

1111 Oakmont Drive #C, San Jose, CA 95117

E-mail: support@inhaos.com

INHAOS China office: :

No.6 Building, Songke Estate, Songshan Lake National Hi-tech Industrial Development Zone, Dongguan, Guangdong Province,

523808,China

E-mail: Support@inhaos.com